TRANSFIELD SERVICES PTY. LTD.

EastLink Ventilation Stack Emission Monitoring Report April-June 2012

Submitted to:

Transfield Services Pty. Ltd., EastLink Operations Centre, 2 Hillcrest Avenue, Ringwood, 3134

This document is issued in accordance with NATA's accreditation requirements. Accredited for compliance with ISO/IEC 17025.

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards.





Report Number.

097613024-024-R-Rev0

Distribution:

1 Electronic Copy - Transfield Services Pty. Ltd.

- 1 Hard Copy Transfield Services Pty. Ltd.
- 1 Hard Copy Golder Associates Pty. Ltd.







Record of Issue

Company	Client Contact	Version	Date Issued	Method of Delivery
Transfield Services Pty. Ltd., EastLink Operations Centre, 2 Hillcrest Avenue, Ringwood, 3134	Ms. Alex Monson	Revision 0	20/07/2012	Post/Electronic





Table of Contents

1.0	INTRO	DUCTION	1
2.0	DISCH	ARGES TO AIR	2
3.0	VENTII	ATION STACK MONITORING PARAMETERS	3
4.0	METHO	DDS	4
	4.1	PM _{2.5}	4
	4.2	PM ₁₀	4
	4.3	Carbon Monoxide	4
	4.4	Oxides of Nitrogen	5
	4.5	Stack Velocity	5
5.0	MEASU	JREMENT UNCERTAINTY	6
6.0	VENTII	ATION STACK EMISSION MONITORING PERIOD: 01/04/2012 – 30/04/2012	7
	6.1	Data Capture	7
	6.2	Results	8
	6.2.1	PM _{2.5}	8
	6.2.2	PM ₁₀	9
	6.2.3	Carbon Monoxide	10
	6.2.4	Oxides of Nitrogen	11
	6.2.4.1	Nitric Oxide	11
	6.2.4.2	Nitrogen Dioxide	12
	6.2.5	Stack Velocity	13
	6.3	Data Validation and Exceptions	14
7.0	VENTII	ATION STACK EMISSION MONITORING PERIOD: 01/05/2012 – 31/05/2012	16
	7.1	Data Capture	16
	7.2	Results	17
	7.2.1	PM _{2.5}	17
	7.2.2	PM ₁₀	18
	7.2.3	Carbon Monoxide	19
	7.2.4	Oxides of Nitrogen	20
	7.2.4.1	Nitric Oxide	20
	7.2.4.2	Nitrogen Dioxide	21





7.2	2.5 Stack Velocity	22
7.3	3 Data Validation and Exceptions	23
8.0 VE	ENTILATION STACK EMISSION MONITORING PERIOD: 01/06/2012 – 30/06/2012	24
8.1	1 Data Capture	24
8.2	2 Results	25
8.2	2.1 PM _{2.5}	25
8.2	2.2 PM ₁₀	26
8.2	2.3 Carbon Monoxide	27
8.2	2.4 Oxides of Nitrogen	28
8.2	2.4.1 Nitric Oxide	28
8.2	2.4.2 Nitrogen Dioxide	29
8.2	2.5 Stack Velocity	30
8.3		
	SCUSSION	
9.1		
TABLES		
	Discharges to Air	2
Table 3:	Measurement Uncertainty	6
Table 4:	Data Capture Statistics - 1 Hour Averages	7
Table 5:	PM _{2.5} Mass Rate Percentiles (1 Hour Average)	8
Table 6:	PM ₁₀ Mass Rate Percentiles (1 Hour Average)	g
Table 7:	Carbon Monoxide Mass Rate Percentiles (1 Hour Average)	10
Table 8:	Nitric Oxide Mass Rate Percentiles (1 Hour Average)	11
Table 9:	Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)	12
Table 10	D: Data Exceptions - Eastern Ventilation Stack: April 2012	14
Table 11	1: Data Exceptions - Western Ventilation Stack: April 2012	15
Table 12	2: Data Capture Statistics - 1 Hour Averages	16
Table 13	3: PM _{2.5} Mass Rate Percentiles (1 Hour Average)	17
Table 14	4: PM ₁₀ Mass Rate Percentiles (1 Hour Average)	18
Table 15	5: Carbon Monoxide Mass Rate Percentiles (1 Hour Average)	19
Table 16	6: Nitric Oxide Mass Rate Percentiles (1 Hour Average)	20
Table 17	7: Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)	21
Table 18	3: Data Exceptions - Eastern Ventilation Stack: May 2012	23
Table 19	9: Data Exceptions - Western Ventilation Stack: May 2012	23





Table 20: Data Capture Statistics - 1 Hour Averages	24
Table 21: PM _{2.5} Mass Rate Percentiles (1 Hour Average)	25
Table 22: PM ₁₀ Mass Rate Percentiles (1 Hour Average)	26
Table 23: Carbon Monoxide Mass Rate Percentiles (1 Hour Average)	27
Table 24: Nitric Oxide Mass Rate Percentiles (1 Hour Average)	28
Table 25: Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)	29
Table 26: Data Exceptions - Eastern Ventilation Stack: June 2012	31
Table 27: Data Exceptions - Western Ventilation Stack: June 2012	31
Table 28: Maximum (1 Hour Average) Mass Rate (01/04/2012 - 30/06/2012)	32
Table 29: Data Capture Year to Date (%)	32
FIGURES	
Figure 1: Ventilation Stack Locations	
Figure 2: PM _{2.5} Mass Rate (1 Hour Average)	
Figure 3: PM ₁₀ Mass Rate (1 Hour Average)	
Figure 4: Carbon Monoxide Mass Rate (1 Hour Average)	
Figure 5: Nitric Oxide Mass Rate (1 Hour Average)	11
Figure 6: Nitrogen Dioxide Mass Rate (1 Hour Average)	12
Figure 7: Stack Velocity (1 Hour Average)	13
Figure 8: PM _{2.5} Mass Rate (1 Hour Average)	17
Figure 9: PM ₁₀ Mass Rate (1 Hour Average)	18
Figure 10: Carbon Monoxide Mass Rate (1 Hour Average)	19
Figure 11: Nitric Oxide Mass Rate (1 Hour Average)	20
Figure 12: Nitrogen Dioxide Mass Rate (1 Hour Average)	21
Figure 13: Stack Velocity (1 Hour Average)	22
Figure 14: PM _{2.5} Mass Rate (1 Hour Average)	25
Figure 15: PM ₁₀ Mass Rate (1 Hour Average)	26
Figure 16: Carbon Monoxide Mass Rate (1 Hour Average)	27
Figure 17: Nitric Oxide Mass Rate (1 Hour Average)	28
Figure 18: Nitrogen Dioxide Mass Rate (1 Hour Average)	29
Figure 19: Stack Valocity (1 Hour Average)	30





1.0 INTRODUCTION

EastLink is a 39-kilometre motorway running between Donvale in Melbourne's north-east to Frankston in Melbourne's south-east with two tunnels under the Mullum Mullum Valley. Transfield Services, who are responsible for operation and maintenance of the road, commissioned Golder Associates Pty. Ltd. to provide continuous emission monitoring services for the EastLink motorway project. The services provided include:

- Operations and maintenance services for the EastLink ventilation stack continuous emission monitoring systems (CEMS)
- NATA endorsed emission monitoring reports.

Monitoring commenced on the 29th June, 2008 with the opening of the EastLink motorway. Results for the sampling period 1st April, 2012 to 30th June, 2012 inclusive are contained in the following report.

The work was conducted under the following Transfield Services Work Order numbers:

Month	West Stack	East Stack
April	453600	453601
May	457456	457457
June	462689	462690





2.0 DISCHARGES TO AIR

EastLink has discharges to air servicing two road tunnels. Discharge Point No. 1 (DP1) services the inbound (Melba) tunnel and Discharge Point No. 2 (DP2) services the outbound (Mullum Mullum) tunnel.

The locations of the discharges to air are described in Table 1 and presented in Figure 1.

Table 1: Discharges to Air

Discharge Point No.	Station Name	Location
1	Western ventilation stack	Western end of inbound tunnel (Melba) - Donvale
2	Eastern ventilation stack	Eastern end of outbound tunnel (Mullum Mullum) – Ringwood

Monitoring equipment is housed in temperature controlled cabinets located at the base of each of the ventilation stacks. Particulate and gaseous sample inlets are installed inside the plenum chamber of each of the ventilation stacks.




Figure 1: Ventilation Stack Locations



3.0 VENTILATION STACK MONITORING PARAMETERS

The following parameters are monitored continuously, with averages logged at 5 minute intervals:

- Particulate matter with an equivalent aerodynamic diameter less than 2.5 microns (PM_{2.5})
- Particulate matter with an equivalent aerodynamic diameter less than 10 microns (PM₁₀)
- Total oxides of nitrogen (NO_x)
- Nitric oxide (NO)
- Nitrogen dioxide (NO₂)
- Carbon monoxide (CO)
- Stack velocity
- Stack temperature
- Ambient pressure.





4.0 METHODS

4.1 PM_{2.5}

PM_{2.5} concentrations in the tunnel ventilation stacks are determined using a 1400 Series Tapered Element Oscillating Microbalance (TEOM) analyser, located in the plenum chamber of the ventilation stacks.

Exhaust gas is drawn through a $PM_{2.5}$ size selective inlet (PM_{10} WINS head fitted with a $PM_{2.5}$ sharp cut cyclone (SCC)) at 1 m³/h. The flow is then isokinetically split into two streams; 1 l/min stream which passes through the filter on the mass transducer and a 15.7 l/min bypass stream.

The sample stream is heated to 50°C to maintain a low and therefore relatively constant humidity.

Measurements are made in real-time (2 s intervals) with the 5-minute averages logged. 1-hour averages are then calculated from the logged data.

The $PM_{2.5}$ monitoring method is based on the requirements of Australian Standard AS 3580.9.8, "Methods for Sampling and Analysis of Ambient Air: Determination of Suspended Particulate Matter – PM_{10} Continuous Direct Mass Method Using a Tapered Element Oscillating Microbalance Analyser".

4.2 PM₁₀

PM₁₀ concentrations in the tunnel ventilation stacks are determined using a 1400 Series Tapered Element Oscillating Microbalance (TEOM) analyser, located in the plenum chamber of the ventilation stacks.

Exhaust gas is drawn through a PM_{10} size selective inlet (PM_{10} WINS head) at 1 m³/h. The flow is then isokinetically split into two streams; 1 l/min stream which passes through the filter on the mass transducer and a 15.7 l/min bypass stream.

The sample stream is heated to 50°C to maintain a low and therefore relatively constant humidity.

Measurements are made in real-time (2 s intervals) with the 5-minute averages logged. 1-hour averages are then calculated from the logged data.

The PM₁₀ monitoring method is based on the requirements of Australian Standard AS 3580.9.8, "Methods for Sampling and Analysis of Ambient Air: Determination of Suspended Particulate Matter – PM₁₀ Continuous Direct Mass Method Using a Tapered Element Oscillating Microbalance Analyser".

4.3 Carbon Monoxide

Carbon monoxide concentrations in the tunnel ventilation stacks are determined by infra-red gas filter correlation analysers.

Automatic calibrations are carried out daily against a NATA certified reference gas mixture. Manual calibrations are conducted at one month intervals.

The carbon monoxide monitoring method is based on the requirements of Australian Standard AS 3580.7.1, "Determination of Carbon Monoxide – Direct Reading Instrumental Method".





4.4 Oxides of Nitrogen

Oxides of nitrogen concentrations in the tunnel ventilation stacks are determined by chemiluminescence gas analysers.

Automatic calibrations are carried out daily against a NATA certified reference gas mixture. Manual calibrations are conducted at one month intervals.

The oxides of nitrogen (NO, NO₂ and NO_x) monitoring method is based on the requirements of Australian Standard AS 3580.5.1, "Determination of Oxides of Nitrogen – Chemiluminescence Method".

4.5 Stack Velocity

Stack gas velocity was determined using an optical flow sensor that complies with USEPA Code of Federal Regulations (CFR 40) Part 75, "Continuous Emission Monitoring" requirements.





5.0 MEASUREMENT UNCERTAINTY

Table 2: Measurement Uncertainty

· · · · · · · · · · · · · · · · · · ·							
Parameter	Method	Estimated Uncertainty					
PM ₁₀	TEOM	± 5%					
PM _{2.5}	TEOM	± 5%					
NO, NO ₂ , NO _X	Chemiluminescence	± 10%					
СО	Infra-red gas filter correlation	± 10%					
Stack velocity	Optical flow sensor	± 0.1 m/s or 5% of reading, whichever is greater					





6.0 VENTILATION STACK EMISSION MONITORING PERIOD: 01/04/2012 - 30/04/2012

6.1 Data Capture

Data capture is defined as the number of valid data periods collected divided by the number of available data periods. Valid data excludes periods where the instrument is unavailable due to calibration and maintenance and excludes periods where the data has been rejected due to quality assurance/data validation procedures.

The data capture statistics for the reporting period 1st April to 30th April, 2012 are shown in Table 3. Averages were only collected for those periods where the 5-minute data constituted 75% data capture.

Section 6.3 provides further information on the reasons for invalid data periods.

Table 3: Data Capture Statistics - 1 Hour Averages

Parameter	Station	Collected Periods	Available Periods	Data Capture
PM _{2.5}	Eastern	512	720	71.1%
	Western	719	720	99.9%
PM ₁₀	Eastern	708	720	98.3%
	Western	718	720	99.7%
NO, NO ₂	Eastern	513	720	71.3%
	Western	687	720	95.4%
00	Eastern	689	720	95.7%
СО	Western	687	720	95.4%





6.2 Results

6.2.1 PM_{2.5}

PM_{2.5} was continuously monitored and 5 minute averages logged. The 5 minute average data was then transformed to 1 hour averages for reporting.

 $PM_{2.5}$ (1 hour average) mass rate of emission statistics for the reporting period are given in Table 4. A plot of $PM_{2.5}$ (1 hour average) mass rate of emission for the reporting period is presented in Figure 2.

Table 4: PM_{2.5} Mass Rate Percentiles (1 Hour Average)

Ctation		l	PM _{2.5} Mass R	ate (kg/h) (1-H	our Average)	
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th
Eastern	0.42	0.32	0.28	0.23	0.20	0.13	0.04
Western	0.28	0.21	0.20	0.16	0.14	0.09	0.03




Figure 2: PM_{2.5} Mass Rate (1 Hour Average)



6.2.2 PM₁₀

 PM_{10} was continuously monitored and 5 minute averages logged. The 5 minute average data was then transformed to 1 hour averages for reporting.

 PM_{10} (1 hour average) mass rate of emission statistics for the reporting period are given in Table 5. A plot of PM_{10} (1 hour average) mass rate of emission for the reporting period is presented in Figure 3.

Table 5: PM₁₀ Mass Rate Percentiles (1 Hour Average)

Station			PM ₁₀ Mass R	ate (kg/h) (1-H	our Average))	
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th
Eastern	0.52	0.34	0.31	0.28	0.24	0.18	0.05
Western	0.46	0.33	0.28	0.22	0.19	0.14	0.05




Figure 3: PM₁₀ Mass Rate (1 Hour Average)



6.2.3 Carbon Monoxide

Carbon monoxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 6. A plot of carbon monoxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 4.

Table 6: Carbon Monoxide Mass Rate Percentiles (1 Hour Average)

Station	Carbon Monoxide Mass Rate (kg/h) (1-Hour Average)						
	Maximum	99 th	98 th	95 th	90 th	75 th	50 th
Eastern	20	19	18	16	12	8.9	5.7
Western	23	20	18	15	13	10	6.8




Figure 4: Carbon Monoxide Mass Rate (1 Hour Average)



6.2.4 Oxides of Nitrogen

6.2.4.1 Nitric Oxide

Nitric oxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 7. A plot of nitric oxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 5.

Table 7: Nitric Oxide Mass Rate Percentiles (1 Hour Average)

Station	Nitric Oxide Mass Rate (kg/h) (1-Hour Average)						
Ctation	Maximum	99 th	98 th	95 th	90 th	75 th	50 th
Eastern	4.0	3.6	3.5	3.0	2.7	2.2	0.9
Western	4.7	4.2	3.7	2.8	2.3	1.9	1.0




Figure 5: Nitric Oxide Mass Rate (1 Hour Average)



6.2.4.2 Nitrogen Dioxide

Nitrogen dioxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 8. A plot of nitrogen dioxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 6.

Table 8: Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)

Station		Nitrogen Dioxide Mass Rate (kg/h) (1-Hour Average)							
Otation	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	0.49	0.43	0.39	0.32	0.29	0.22	0.10		
Western	0.39	0.33	0.30	0.24	0.20	0.16	0.08		




Figure 6: Nitrogen Dioxide Mass Rate (1 Hour Average)





6.2.5 Stack Velocity

The stack velocity (1 hour average) plot for the reporting period is presented in Figure 7.




Figure 7: Stack Velocity (1 Hour Average)



6.3 Data Validation and Exceptions

Data contained in the report has been validated against performance and calibration requirements for each instrument. Data during maintenance and calibration periods has been removed from the validated data sets. Tables 9 and 10 list the data exceptions for the eastern and western ventilation stacks respectively. Data during automatic calibrations of the gaseous atmospheric contaminants has also been removed from the data sets.

Table 9: Data Exceptions - Eastern Ventilation Stack: April 2012

Start	End	Parameter	Reason
1/04/2012 0:00	1/04/2012 23:55	NO, NO ₂ , NO _x	Invalid data - Span drift
2/04/2012 11:15	2/04/2012 11:35	Velocity	Maintenance/calibration
4/04/2012 7:15	6/04/2012 9:50	NO, NO ₂ , NO _x	Invalid data - Span drift
9/04/2012 10:15	9/04/2012 10:35	NO, NO ₂ , NO _x	Maintenance/calibration
12/04/2012 16:30	12/04/2012 17:10	PM _{2.5}	Invalid data ¹
13/04/2012 0:40	16/04/2012 23:55	NO, NO ₂ , NO _x	Invalid data - Span drift
14/04/2012 13:55	14/04/2012 15:05	PM _{2.5}	Invalid data ¹
14/04/2012 18:25	14/04/2012 20:30	PM _{2.5}	Invalid data ¹
14/04/2012 22:35	14/04/2012 23:20	PM _{2.5}	Invalid data ¹
15/04/2012 17:15	15/04/2012 17:50	PM _{2.5}	Invalid data ¹
16/04/2012 13:40	16/04/2012 14:35	PM _{2.5}	Maintenance/calibration
16/04/2012 22:25	16/04/2012 22:50	PM _{2.5}	Invalid data1
19/04/2012 20:20	19/04/2012 20:50	PM _{2.5}	Invalid data ¹
22/04/2012 6:30	22/04/2012 11:00	PM _{2.5}	Invalid data ¹
22/04/2012 14:30	22/04/2012 14:45	PM _{2.5}	Invalid data ¹
22/04/2012 19:40	22/04/2012 23:55	PM _{2.5}	Invalid data1
23/04/2012 3:00	23/04/2012 14:30	PM _{2.5}	Invalid data ¹
23/04/2012 13:45	23/04/2012 17:00	PM ₁₀	Maintenance/calibration
23/04/2012 20:45	24/04/2012 4:20	PM ₁₀	Invalid data ¹
24/04/2012 0:40	24/04/2012 10:30	NO, NO_2, NO_x	Invalid data - Span drift
24/04/2012 4:35	24/04/2012 5:00	PM _{2.5}	Invalid data ¹
24/04/2012 9:55	24/04/2012 10:25	со	Maintenance/calibration
24/04/2012 10:30	24/04/2012 11:30	PM _{2.5}	Maintenance/calibration
24/04/2012 11:30	30/04/2012 23:55	PM _{2.5}	Invalid data1
24/04/2012 12:00	24/04/2012 12:25	PM ₁₀	Maintenance/calibration
24/04/2012 19:45	24/04/2012 20:00	PM ₁₀	Invalid data ¹
25/04/2012 7:00	25/04/2012 7:10	NO, NO ₂ , NO _x	Maintenance/calibration
30/04/2012 14:45	30/04/2012 16:20	NO , NO_2 , NO_x	Maintenance/calibration

Note: ¹ – In the opinion of the reviewer.





Table 10: Data Exceptions - Western Ventilation Stack: April 2012

Start	End	Parameter	Reason
6/04/2012 3:50	6/04/2012 4:00	PM ₁₀	Invalid data ¹
6/04/2012 9:20	6/04/2012 9:45	СО	Maintenance/calibration
24/04/2012 12:15	24/04/2012 13:20	СО	Maintenance/calibration
24/04/2012 12:50	24/04/2012 13:25	PM _{2.5}	Maintenance/calibration
24/04/2012 13:00	24/04/2012 13:45	NO, NO ₂ , NO _x	Maintenance/calibration
24/04/2012 13:05	24/04/2012 13:55	PM ₁₀	Maintenance/calibration
30/04/2012 13:00	30/04/2012 14:20	NO, NO ₂ , NO _x	Maintenance/calibration
30/04/2012 13:20	30/04/2012 13:25	PM _{2.5}	Maintenance/calibration
30/04/2012 13:20	30/04/2012 13:45	PM ₁₀	Maintenance/calibration

Note: ¹ – In the opinion of the reviewer.



7.0 VENTILATION STACK EMISSION MONITORING PERIOD: 01/05/2012 – 31/05/2012

7.1 Data Capture

Data capture is defined as the number of valid data periods collected divided by the number of available data periods. Valid data excludes periods where the instrument is unavailable due to calibration and maintenance and excludes periods where the data has been rejected due to quality assurance/data validation procedures.

The data capture statistics for the reporting period 1st May to 31st May, 2012 are shown in Table 11. Averages were only collected for those periods where the 5-minute data constituted 75% data capture.

Section 7.3 provides further information on the reasons for invalid data periods.

Table 11: Data Capture Statistics - 1 Hour Averages

Parameter	Station	Collected Periods	Available Periods	Data Capture
DM	Eastern	677	744	91.0%
PM _{2.5}	Western	730	744	98.1%
PM ₁₀	Eastern	743	744	99.9%
1 14110	Western	741	744	99.6%
NO NO	Eastern	712	744	95.7%
NO, NO ₂	Western	710	744	95.4%
СО	Eastern	712	744	95.7%
	Western	711	744	95.6%





7.2 Results

7.2.1 PM_{2.5}

PM_{2.5} was continuously monitored and 5 minute averages logged. The 5 minute average data was then transformed to 1 hour averages for reporting.

 $PM_{2.5}$ (1 hour average) mass rate of emission statistics for the reporting period are given in Table 12. A plot of $PM_{2.5}$ (1 hour average) mass rate of emission for the reporting period is presented in Figure 8.

Table 12: PM_{2.5} Mass Rate Percentiles (1 Hour Average)

Ctatian		PM _{2.5} Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	0.26	0.21	0.20	0.18	0.16	0.12	0.04		
Western	0.23	0.20	0.19	0.14	0.12	0.09	0.04		




Figure 8: PM_{2.5} Mass Rate (1 Hour Average)



7.2.2 PM₁₀

 PM_{10} was continuously monitored and 5-minute averages logged. The 5 minute average data was then transformed to 1 hour averages for reporting.

 PM_{10} (1 hour average) mass rate of emission statistics for the reporting period are given in Table 13. A plot of PM_{10} (1 hour average) mass rate of emission for the reporting period is presented in Figure 9.

Table 13: PM₁₀ Mass Rate Percentiles (1 Hour Average)

Ctation		PM ₁₀ Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	0.33	0.28	0.26	0.23	0.21	0.16	0.06		
Western	0.46	0.35	0.31	0.25	0.20	0.15	0.07		




Figure 9: PM₁₀ Mass Rate (1 Hour Average)



7.2.3 Carbon Monoxide

Carbon monoxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 14. A plot of carbon monoxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 10.

Table 14: Carbon Monoxide Mass Rate Percentiles (1 Hour Average)

Station	Carbon Monoxide Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th	
Eastern	20	19	18	16	13	10	6.9	
Western	22	19	18	15	11	8.5	6.5	




Figure 10: Carbon Monoxide Mass Rate (1 Hour Average)



7.2.4 Oxides of Nitrogen

7.2.4.1 Nitric Oxide

Nitric oxide (1-hour average) mass rate of emission statistics for the reporting period are given in Table 15. A plot of nitric oxide (1-hour average) mass rate of emission for the reporting period is presented in Figure 11.

Table 15: Nitric Oxide Mass Rate Percentiles (1 Hour Average)

Station	Nitric Oxide Mass Rate (kg/h) (1-Hour Average)						
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th
Eastern	4.2	3.9	3.7	3.2	2.8	2.4	1.2
Western	5.0	4.3	4.1	3.1	2.5	2.0	1.3




Figure 11: Nitric Oxide Mass Rate (1 Hour Average)



7.2.4.2 Nitrogen Dioxide

Nitrogen dioxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 16. A plot of nitrogen dioxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 12.

Table 16: Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)

Ctation		Nitrogen Dioxide Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	0.49	0.43	0.44	0.37	0.32	0.27	0.15		
Western	0.43	0.37	0.34	0.24	0.20	0.16	0.11		




Figure 12: Nitrogen Dioxide Mass Rate (1 Hour Average)





7.2.5 Stack Velocity

The stack velocity (1 hour average) plot for the reporting period is presented in Figure 13.




Figure 13: Stack Velocity (1 Hour Average)



7.3 Data Validation and Exceptions

Data contained in the report has been validated against performance and calibration requirements for each instrument. Data during maintenance and calibration periods has been removed from the validated data sets. Tables 17 and 18 list the data exceptions for the eastern and western ventilation stacks respectively. Data during automatic calibrations of the gaseous atmospheric contaminants has also been removed from the data sets.

Table 17: Data Exceptions - Eastern Ventilation Stack: May 2012

Start	End	Parameter	Reason
1/05/2012 0:00	3/05/2012 11:35	PM _{2.5}	Invalid data ¹
3/05/2012 11:35	3/05/2012 14:45	PM _{2.5}	Maintenance/calibration
4/05/2012 10:50	4/05/2012 13:10	PM _{2.5}	Maintenance/calibration
14/05/2012 13:50	14/05/2012 14:25	PM _{2.5}	Maintenance/calibration
14/05/2012 13:30	14/05/2012 14:05	NO, NO ₂ , NO _x	Maintenance/calibration
14/05/2012 13:30	14/05/2012 13:45	СО	Maintenance/calibration
14/05/2012 14:00	14/05/2012 14:50	PM ₁₀	Maintenance/calibration
15/05/2012 17:15	15/05/2012 17:50	PM _{2.5}	Invalid data ¹
22/05/2012 14:25	22/05/2012 15:05	Velocity	Maintenance/calibration
23/05/2012 10:40	23/05/2012 11:00	Velocity	Maintenance/calibration
30/05/2012 12:45	30/05/2012 13:05	NO, NO ₂ , NO _x	Maintenance/calibration

Note: ¹ – In the opinion of the reviewer.

Table 18: Data Exceptions - Western Ventilation Stack: May 2012

Start	End	Parameter	Reason
7/05/2012 11:15	7/05/2012 11:40	NO, NO ₂ , NO _x	Maintenance/calibration
7/05/2012 11:25	7/05/2012 12:00	PM _{2.5}	Maintenance/calibration
10/05/2012 12:30	10/05/2012 12:45	PM _{2.5}	Invalid data ¹
11/05/2012 12:25	11/05/2012 13:00	PM _{2.5}	Maintenance/calibration
14/05/2012 9:10	14/05/2012 9:50	NO, NO ₂ , NO _x	Maintenance/calibration
14/05/2012 9:40	14/05/2012 10:15	СО	Maintenance/calibration
14/05/2012 9:40	14/05/2012 13:05	PM _{2.5}	Maintenance/calibration
14/05/2012 10:25	14/05/2012 12:15	PM ₁₀	Maintenance/calibration
15/05/2012 12:50	15/05/2012 14:00	PM _{2.5}	Maintenance/calibration
16/05/2012 6:35	16/05/2012 8:20	PM _{2.5}	Maintenance/calibration
17/05/2012 11:10	17/05/2012 13:05	PM _{2.5}	Maintenance/calibration
17/05/2012 14:20	17/05/2012 14:35	PM _{2.5}	Maintenance/calibration
18/05/2012 7:15	18/05/2012 7:45	NO, NO ₂ , NO _x	Maintenance/calibration

Note: ¹ – In the opinion of the reviewer.





8.0 VENTILATION STACK EMISSION MONITORING PERIOD: 01/06/2012 - 30/06/2012

8.1 Data Capture

Data capture is defined as the number of valid data periods collected divided by the number of available data periods. Valid data excludes periods where the instrument is unavailable due to calibration and maintenance and excludes periods where the data has been rejected due to quality assurance/data validation procedures.

The data capture statistics for the reporting period 1st June to 30th June, 2012 are shown in Table 19. Averages were only collected for those periods where the 5 minute data constituted 75% data capture.

Section 8.3 provides further information on the reasons for invalid data periods.

Table 19: Data Capture Statistics - 1 Hour Averages

Parameter	Station	Collected Periods	Available Periods	Data Capture
	Eastern	718	720	99.7%
PM _{2.5}	Western	717	720	99.6%
PM ₁₀	Eastern	718	720	99.7%
1 10110	Western	718	720	99.7%
NO, NO ₂	Eastern	686	720	95.3%
NO, NO ₂	Western	683	720	94.9%
00	Eastern	688	720	95.6%
СО	Western	687	720	95.4%





8.2 Results

8.2.1 PM_{2.5}

PM_{2.5} was continuously monitored and 5-minute averages logged. The 5-minute average data was then transformed to 1-hour averages for reporting.

 $PM_{2.5}$ (1-hour average) mass rate of emission statistics for the reporting period are given in Table 20. A plot of $PM_{2.5}$ (1-hour average) mass rate of emission for the reporting period is presented in Figure 14.

Table 20: PM_{2.5} Mass Rate Percentiles (1 Hour Average)

Ctation	PM _{2.5} Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th	
Eastern	0.24	0.18	0.17	0.15	0.14	0.10	0.03	
Western	0.23	0.20	0.18	0.14	0.11	0.08	0.03	




Figure 14: PM_{2.5} Mass Rate (1 Hour Average)



8.2.2 PM₁₀

 PM_{10} was continuously monitored and 5 minute averages logged. The 5 minute average data was then transformed to 1-hour averages for reporting.

 PM_{10} (1 hour average) mass rate of emission statistics for the reporting period are given in Table 21. A plot of PM_{10} (1 hour average) mass rate of emission for the reporting period is presented in Figure 15.

Table 21: PM₁₀ Mass Rate Percentiles (1 Hour Average)

Ctation	PM₁₀ Mass Rate (kg/h) (1-Hour Average)								
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	0.35	0.26	0.26	0.23	0.20	0.15	0.05		
Western	0.87	0.30	0.26	0.22	0.19	0.13	0.05		




Figure 15: PM₁₀ Mass Rate (1 Hour Average)



8.2.3 Carbon Monoxide

Carbon monoxide (1 hour average) mass rate of emission statistics for the reporting period are given in Table 22. A plot of carbon monoxide (1 hour average) mass rate of emission for the reporting period is presented in Figure 16.

Table 22: Carbon Monoxide Mass Rate Percentiles (1 Hour Average)

Ctation	Carbon Monoxide Mass Rate (kg/h) (1-Hour Average)								
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th		
Eastern	20	19	18	16	13	9.5	7.0		
Western	21	19	17	14	11	8.8	6.8		




Figure 16: Carbon Monoxide Mass Rate (1 Hour Average)



8.2.4 Oxides of Nitrogen

8.2.4.1 Nitric Oxide

Nitric oxide (1-hour average) mass rate of emission statistics for the reporting period are given in Table 23. A plot of nitric oxide (1-hour average) mass rate of emission for the reporting period is presented in Figure 17.

Table 23: Nitric Oxide Mass Rate Percentiles (1 Hour Average)

Station	Nitric Oxide Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th	
Eastern	4.2	3.7	3.5	3.1	2.7	2.2	1.1	
Western	4.7	4.4	3.9	2.9	2.5	1.9	1.1	




Figure 17: Nitric Oxide Mass Rate (1 Hour Average)



8.2.4.2 Nitrogen Dioxide

Nitrogen dioxide (1-hour average) mass rate of emission statistics for the reporting period are given in Table 24. A plot of nitrogen dioxide (1-hour average) mass rate of emission for the reporting period is presented in Figure 18.

Table 24: Nitrogen Dioxide Mass Rate Percentiles (1 Hour Average)

Ctation	Nitrogen Dioxide Mass Rate (kg/h) (1-Hour Average)							
Station	Maximum	99 th	98 th	95 th	90 th	75 th	50 th	
Eastern	0.49	0.45	0.43	0.36	0.32	0.25	0.14	
Western	0.41	0.37	0.31	0.22	0.19	0.15	0.09	




Figure 18: Nitrogen Dioxide Mass Rate (1 Hour Average)





8.2.5 Stack Velocity

The stack velocity (1 hour average) plot for the reporting period is presented in Figure 19.




Figure 19: Stack Velocity (1 Hour Average)





8.3 Data Validation and Exceptions

Data contained in the report has been validated against performance and calibration requirements for each instrument. Data during maintenance and calibration periods has been removed from the validated data sets. Tables 25 and 26 list the data exceptions for the eastern and western ventilation stacks respectively. Data during automatic calibrations of the gaseous atmospheric contaminants has also been removed from the data sets.

Table 25: Data Exceptions - Eastern Ventilation Stack: June 2012

Start	End	Parameter	Reason
4/06/2012 7:10	4/06/2012 7:35	NO, NO ₂ , NO _x	Maintenance/calibration
6/06/2012 14:55	6/06/2012 15:15	NO, NO ₂ , NO _x	Maintenance/calibration
6/06/2012 14:55	6/06/2012 15:15	со	Maintenance/calibration
20/06/2012 13:50	20/06/2012 14:35	Velocity	Maintenance/calibration
20/06/2012 15:00	20/06/2012 15:10	со	Maintenance/calibration
20/06/2012 15:15	20/06/2012 15:20	NO, NO ₂ , NO _x	Maintenance/calibration
21/06/2012 4:25	21/06/2012 8:50	Velocity	Instrument out of service
22/06/2012 4:25	22/06/2012 9:20	Velocity	Instrument out of service
22/06/2012 20:55	22/06/2012 23:55	Velocity	Instrument out of service
23/06/2012 5:25	23/06/2012 8:45	Velocity	Instrument out of service
24/06/2012 6:30	24/06/2012 7:25	Velocity	Instrument out of service
24/06/2012 7:35	24/06/2012 7:35	Velocity	Instrument out of service
25/06/2012 4:25	25/06/2012 5:20	Velocity	Instrument out of service
26/06/2012 4:30	26/06/2012 5:35	Velocity	Instrument out of service
26/06/2012 14:40	26/06/2012 15:10	NO, NO ₂ , NO _x	Maintenance/calibration
26/06/2012 14:45	26/06/2012 16:35	PM _{2.5}	Maintenance/calibration
26/06/2012 16:05	26/06/2012 17:55	PM ₁₀	Maintenance/calibration
27/06/2012 4:30	27/06/2012 8:55	Velocity	Instrument out of service
28/06/2012 4:30	28/06/2012 9:25	Velocity	Instrument out of service
28/06/2012 8:15	28/06/2012 9:10	NO, NO ₂ , NO _x	Maintenance/calibration
28/06/2012 8:15	28/06/2012 9:10	со	Maintenance/calibration
29/06/2012 4:30	29/06/2012 9:15	Velocity	Instrument out of service
30/06/2012 6:25	30/06/2012 9:45	Velocity	Instrument out of service

Table 26: Data Exceptions - Western Ventilation Stack: June 2012

Start	End	Parameter	Reason
1/06/2012 7:15	1/06/2012 7:45	NO, NO ₂ , NO _x	Maintenance/calibration
6/06/2012 13:40	6/06/2012 14:05	СО	Maintenance/calibration
6/06/2012 14:10	6/06/2012 14:30	NO, NO ₂ , NO _x	Maintenance/calibration
26/06/2012 10:00	26/06/2012 12:40	PM _{2.5}	Maintenance/calibration
26/06/2012 12:10	26/06/2012 13:50	PM ₁₀	Maintenance/calibration
27/06/2012 8:35	27/06/2012 9:40	NO, NO ₂ , NO _x	Maintenance/calibration
27/06/2012 9:40	27/06/2012 10:50	СО	Maintenance/calibration
27/06/2012 10:35	27/06/2012 12:45	NO, NO ₂ , NO _x	Maintenance/calibration





9.0 DISCUSSION

9.1 Comparison with Licence Limits

EastLink emissions to air from the road tunnel ventilation stacks DP1 and DP2 are subject to the licence requirements contained in Environment Protection Authority (Victoria) Waste Discharge Licence No. EA 63607.

The maximum measured 1 hour average mass rate for each parameter is compared with the applicable licence limit in Table 27.

Table 27: Maximum (1 Hour Average) Mass Rate (01/04/2012 - 30/06/2012)

Discharge	Maximum (1 flour Average) mass rate (01/04/2012 - 30/00/2012)						
Point No.	Discharge Description	Compound	Mass Rate (kg/h)	Licence Limit (kg/h)			
1	Western ventilation stack	PM _{2.5}	0.28	2.4			
		PM ₁₀	0.87	2.6			
		NO ₂	0.43	3.98			
		CO	23	112			
2	Eastern ventilation stack	PM _{2.5}	0.42	2.4			
		PM ₁₀	0.52	2.6			
		NO ₂	0.49	3.98			
		CO	20	112			

There were no exceedences of the licence limits for DP1 and DP2 during the reporting period.

Data capture statistics for 2012 year to date (01/01/2012 – 30/06/2012) are presented in Table 28.

Table 28: Data Capture Year to Date (%)

Station	NO ₂	СО	PM _{2.5}	PM ₁₀	Velocity
Eastern	92.0	97.3	91.3	99.6	99.0
Western	92.0	95.5	99.0	99.2	100





Report Signature Page

GOLDER ASSOCIATES PTY LTD

Anthony Myszka Environmental Technician Mark Tulau Senior Air Quality Specialist

MD ful.

AM/MT/slh

A.B.N. 64 006 107 857

Golder, Golder Associates and the GA globe design are trademarks of Golder Associates Corporation.

- End of Report -



At Golder Associates we strive to be the most respected global company providing consulting, design, and construction services in earth, environment, and related areas of energy. Employee owned since our formation in 1960, our focus, unique culture and operating environment offer opportunities and the freedom to excel, which attracts the leading specialists in our fields. Golder professionals take the time to build an understanding of client needs and of the specific environments in which they operate. We continue to expand our technical capabilities and have experienced steady growth with employees who operate from offices located throughout Africa, Asia, Australasia, Europe, North America, and South America.

Africa + 27 11 254 4800
Asia + 86 21 6258 5522
Australasia + 61 3 8862 3500
Europe + 356 21 42 30 20
North America + 1 800 275 3281
South America + 55 21 3095 9500

solutions@golder.com www.golder.com

Golder Associates Pty Ltd Building 7, Botanicca Corporate Park 570 – 588 Swan Street Richmond, Victoria 3121 Australia

T: +61 3 8862 3500

